

# Kodak PIXPRO

Digital Cameras

## ASTRO ZOOM AZ422



### FEATURES:

Passion and performance go hand in hand with our KODAK PIXPRO AZ422 digital camera from the Astro Zoom Collection. A 42x ultra long zoom lens with optical image stabilization delivers crisp, clear 20 megapixel close-ups, panorama or HD videos. Auto scene, object tracking, post-editing features and a host of powerful yet user-friendly settings make photography easy, fun and zero hassle. KODAK PIXPRO Digital Cameras – Tell your story.

- 42X Optical Zoom
- 24mm Wide Angle
- 20 Megapixels
- 3" LCD
- 720p HD Video
- OIS (Optical Image Stabilization)
- Li-ion Battery



Images are simulated.

Available Colors:



**42X**  
OPTICAL  
ZOOM

**24mm**  
WIDE

**20MP**

**3"**  
7.6CM

**HD**

**Panorama  
Capture**

# Kodak

## PIXPRO AZ422

Digital Camera

42X  
OPTICAL  
ZOOM

24mm  
WIDE

20MP

3"  
7.6cm

HD

Panorama  
Capture

### SPECIFICATIONS

### AZ422

Effective Image Sensor Pixels	20.16 Megapixels
Total Image Sensor Pixels	20.48 Megapixels [1/2.3"(CCD)]
Lens	
Focal Length	4.3 mm (Wide) — 180.6 mm (Tele)
[ 35mm film equivalent ]	[24 mm (Wide) — 1008 mm (Tele)]
F number	F3.0 (Wide) — F6.8 (Tele)
Lens Construction	11 groups 15 elements
Optical Zoom	42x
Focusing Range	Normal: (Wide) 50 cm — ∞, (Tele) 200 cm — ∞ Macro: 1.6 cm — ∞ (Wide Only)
Autofocus System	TTL Autofocus
Anti-Handshake	OIS (Optical Image Stabilization)
Digital Zoom	4x Digital Zoom (Combined Zoom: 168x)
Number of Recording Pixels	
Still Image	(4:3) 20MP: 5152x3864, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 17MP: 5152x3432, (16:9) 15MP: 5152x3864, 2MP: 1920x1080
Movie	1280x720: 30fps / 15fps, 640x480: 30fps
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: H.264; Audio: Linear PCM (Monaural)]
Shooting Modes	Auto, P, S, A, M, Face Beautifier, Panorama, Movie, CS
SCN Modes	ASCN, Landscape, Sport, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
HDR	Yes
Panorama	Up to 180° (Horizontal)
LCD Display	3.0 inch (460K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600/3200 (4M)
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 - 30 Seconds
Continuous Shooting	Yes
Playback Modes	Single, Index (9/16 Thumbnails), Slide Show, Date, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)
Flash	
Flash Method	Pop-up (Manual)
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Force Off
Shooting Range	(Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800)
Recording Media	Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported]
Other Features	Eye-Fi® Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Power	Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 200 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 4.44 x 3.21 x 3.32 in. / 112.7 x 81.6 x 84.4 mm (Based on CIPA Standards)
Weight	Approx. Approx. 15.67 oz. / 444g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, USB Cable, Neck Strap, Lens Cover, Service Card, Quick Start Guide, Warranty

## JK Imaging Ltd.

JK Imaging Ltd.  
17239 South Main Street  
Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras:  
visit: [kodakpixpro.com](http://kodakpixpro.com)

