KODAK PIXPRO SP360

ACTION CAM

PIXPRO Supported Software

Desktop Editing Software, Deskstop Stitch Software















SP360 1080p

See and experience your world in a whole new light. Introducing the KODAK PIXPRO SP360 Action Cam designed not only to capture what you love to do, but much more of it. Immerse yourself and record 360° spherical VR video on the fly. Facebook™ and YouTube™ compatibility to share your 360° VR videos and photos with the world is right at the tip of your fingers. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 360° Spherical Curved Lens / 214° FOV
- 16MP CMOS
- Full HD 1080p Video
- 10 fps Burst Shooting
- Shockproof / Splashproof / Freezeproof / Dustproof
- Wi-Fi / NFC Connectivity
- Control Wirelessly with iOS[™] / Android[™] Smart Device APP





*SP360 supports YouTube 360° Video















Available Colors:



YELLOW



KODAK PIXPRO SP360

ACTION CAM

SPECIFICATIONS	SP360
Effective Image Sensor Pixels	16.36 Megapixels
Total Image Sensor Pixels	17.52 Megapixels [1/2.33" CMOS]
Lens	
Focal Length	0.805 mm
[35mm film equivalent]	[8.25 mm]
F number	F2.8
Lens Construction	7 groups 9 elements
Field of View	Max. 214 Degree (Without Protective Lens Cover)
Focusing Range	50 cm — ∞
Anti-Handshake	Electronic Image Stabilization (EIS)
Number of Recording Pixels	(44) 40 MD 2004 (40) EMD 2004 (40) EMD 2004 40 M (400) AMD 4000 4000
Still Image	(1:1) 10MP: 3264x3264, (4:3) 5MP: 2592x1944, (16:9) 2MP: 1920x1080
Movie	1920x1080: 30fps, 1440x1440: 30fps, 1072x1072: 30fps, 1280x960: 50fps / 30fps, 1280x720: 60fps / 30fps, 848x480: 60fps High Speed Movie: 848x480: 120fps
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MP4 [Image: H.264; Audio: AAC [Stereo]
Shooting Modes	Still, Burst Shot, Movie, Time Lapse, Loop Recording, Wi-Fi
Splashproof	Equivalent to JIS/IEC (IPX5) (Body)
Shockproof	Up to 2m (With Protective Lens Cover)
Dustproof	Equivalent to JIS/IEC (IP6X)
Freeze-proofing	14° F / -10° C
Status LCD	1.0 inch TN LCD
ISO Sensitivity	Auto, (100 - 800)
Exposure Metering Method	Artificial Intelligence AE (AiAE)
Exposure Contol Method	Program AE
Burst Mode	Approx. 10fps (Full Resolution)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Underwater
Recording Media	Internal Memory: Approx. 8MB, Micro SD/Micro SDHC Card (Up to 32GB Support), Class 6 Card or Better [MMC Card Not Supported]
Language Support	English
Jacks	USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Wi-Fi	Yes (802.11 b/g/n)
NFC	Yes
Remote Control	Yes (via Smart Device)
Power	Rechargeable Li-ion Battery (LB-080), 3.6V 1250mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 350 Shots (Based on CIPA Standards) Approx. 160 min. for Video (@ 1080p/30fps)
Operation Environment	Temperature: 14° – 104°F / -10° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 1.61 x 1.96 x 1.49 in. / 41.1 x 50.0 x 52.1 mm without glass lens cover (Based on CIPA Standards)
Weight	Approx. 3.63 oz. / 103g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, USB Cable, AC Adapter, Quick Start Guide, Warranty Card, Service Card, Plastic Lens Cover, Protective Cover, Battery Charger, Carrying Case, Cleaning Cloth
Compatible Devices	iOS™ Devices (version 8.0 and up) / Android™ Devices (version 4.2 and up)





JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806

© 2017 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0025.0817.en.07

To learn more about KODAK PIXPRO Digital Cameras:

visit: kodakpixpro.com











