

KODAK PIXPRO AZ255

DIGITAL CAMERA



AZ255 ASTRO ZOOM

Discover the new collection of KODAK PIXPRO Digital Cameras and discover a world of creativity at your fingertips. The AZ255 is the perfect bridge camera to explore your love of photography. Ample mega pixels, 25X optical mega zoom and a wider angle lens than traditional models, this camera could easily become your new best friend. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 25X Optical Zoom
- 1080p Full HD Video
- 16MP
- 24mm Wide Angle
- OIS (Optical Image Stabilization)
- 3" LCD (460K Pixels)
- AA Battery

25X
Optical
Zoom

24mm
WIDE

16MP

3" LCD

1080p
Full HD

Panorama
Capture



Available Colors:

- BLACK
- RED
- WHITE

Images are simulated.



KODAK PIXPRO AZ255

DIGITAL CAMERA

SPECIFICATIONS	AZ255
Effective Image Sensor Pixels	16.35 Megapixels
Total Image Sensor Pixels	16.76 Megapixels [1/2.3" BSI CMOS]
Lens	
Focal Length	4.3 mm (Wide) — 107.5 mm (Tele)
[35mm film equivalent]	[24 mm (Wide) — 600 mm (Tele)]
F number	F3.7 (Wide) — F6.2 (Tele)
Lens Construction	11 groups 12 elements
Optical Zoom	25x
Focusing Range	Normal: (Wide) 60 cm — ∞, (Tele) 250 cm — ∞ Macro: 3 cm — ∞ (Wide Only)
Anti-Shake	OIS (Optical Image Stabilization)
Digital Zoom	4x Digital Zoom (Combined Zoom: 100x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1920x1080(30fps), 1280x720(60/30fps), 640x480(30fps), High-Speed Movie: 640x480(120fps)
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: Motion JPEG; Audio: Linear PCM (Monaural)]
Shooting Modes	Auto, P, S, A, M, Face Beautifier, Panorama, SCN, Movie, CS
SCN Modes	ASCN, Sport, Beach, Landscape, Sunset, Fireworks, Night Landscape, Snow, Children, Party, Portrait, Night Portrait, Pet
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
HDR	Yes
Scan Panorama	Up to 360°
LCD Display	3.0 inch (460K Pixels)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available), Shutter Prior AE, Aperture Prior AE
Exposure Compensation	+/- 3EV in 1/3 Step Increments
Shutter Speed	1/2000 – 30 Seconds
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Burst Shooting, Zoom (Approx. x2 – x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)
Flash	
Flash Method	Pop-up (Manual)
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.5 m – 7.1 m (ISO800); (Tele) Approx. 2.5 m – 4.2 m (ISO800)
Recording Media	Internal Memory: Approx. 67MB SD/SDHC/SDXC Card (Up to 512GB Support) [MMC Card not supported]
Other Features	Multi-Language Support (27 Languages)
Jacks	USB 2.0 (Micro 5 pin USB)
Power	AA Alkaline Battery (x4) AA NiMH Battery (x4) (Not Included)
Shooting Capability (Battery Performance)	Approx. 300 Shots of AA Alkaline Battery (Based on CIPA Standards) Approx. 120 Min. of Video (@ 1080/30fps)
Operation Environment	Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 4.47 x 3.06 x 2.74 in. / 113.6 x 77.7 x 69.7 mm (Based on CIPA Standards)
Weight	Approx. 12.5 oz. / 336g (Body Only)
Supplied Accessories	AA Alkaline Battery(x4), USB Cable, Neck Strap, Lens Cover, Quick Start Guide, Warranty Card, Service Card

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248
(888) 978-0806

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

© 2022 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0067.0822.en.01

